


# TELONG ENERGY TECHNOLOGY CO., LTD.

Anjia Industrial Zone, HuanGuan South Road, GuanLan Town, ShenZhen City, GuangDong Province, China

TEL:+86-755-29052355 FAX:+86-755-27981742 E-mail:[telongbattery@sztlg.com](mailto:telongbattery@sztlg.com) <http://www.sztlg.com>

## CR26500 Lithium Manganese Dioxide Battery


### TECHNICAL DATA




Characteristics: ( $23 \pm 2^\circ\text{C}$ )

Nominal capacity (10mA-4.0V) .....	5000mAh
Nominal voltage .....	3.0V
Max. constant current.....	2000mA
Max. pulse current.....	3000mA
Weight.....	62g
Volume.....	$\Phi 26.0 \times 50.0$ mm
Workable temperature.....	$-40^\circ\text{C} \sim +70^\circ\text{C}$


### TECHNICAL CHARACTERISTICS



Discharge Characteristics



Temperature Characteristics



Load-Capacity Characteristics

#### Caution:

Do not make the battery short-circuit, nor charge, press, disassemble, burn or forcibly discharge it; Do not use new and used batteries together nor mix different types of batteries; Do not reverse the positive and negative pole of battery while using it; Do not solder directly on battery.